

L5F FIXED LPR CAMERA SYSTEM

**SEE FARTHER.
SEE CLEARER.
SCAN MORE.**

Missed scans mean unsolved cases and unrecognized revenue. The L5F Fixed License Plate Recognition Camera System captures clearer images at greater distances on your high-speed, high-volume roadways. Paired with ClientPortal, this solution enables you to receive real-time alerts, conduct comprehensive searches and leverage advanced analytics and parking tools to uncover new vehicle location insights that protect communities and generate revenue.

KEY FEATURES

Scan More Than Before

Capture your clearest plate detections yet, at greater distance, on your most high-volume, high-speed roadways.

Rely On Better Basics

Beyond ensuring you've captured the best data, we make management, alerting and searching straight-forward.

Do More With More Data

Use patented analytics, specialized tools as well as easier data sharing and access to derive new intelligent insights.



L5F FIXED LPR CAMERA

The L5F Camera features a new state-of-the-art sensor that allows it to capture clearer images at greater distances on your high-speed, high-volume roadways.



CAMERA PERFORMANCE

Part Number	Optimal Focal Length	Capture Range
VSR-5x-908	14 ft	6-27 ft
VSR-5x-916	40 ft	25-55 ft
VSR-5x-925	70 ft	55-85 ft
VSR-5x-935	95 ft	85-105 ft
VSR-5x-950	115 ft	105-125 ft

OPTICS

Window	Shatterproof window	
Resolution	1440x1080 Monochrome global shutter	1440x1080 Color global shutter
Capture speed maximum	150 mph (241 kph)	

ILLUMINATION

Pulsed LED illumination	Zero lux environments *850nm and 750nm options
-------------------------	--

VIDEO STREAMING

ONVIF compliant	H.264/H.265, M JPEG
-----------------	---------------------

HOUSING

Size	6.9 x 6.5 x 2 in / 175 x 165 x 51 mm
Fixed mounting	3-axis (aim precision) lock in place, low profile, solid mount, and sun shield
Color	Matte black
Weight	3.5 lbs

ENVIRONMENTAL

Environmental protection	IP67 / NEMA4 compliant
Operational temperature	-40°F to 140°F (-40°C to 65°C)
Connector	IP67 rated

ELECTRICAL

Power consumption	12.95W nominal
Input voltage	POE (IEEE802.3 af PD)

CABLE MANAGEMENT

Cable length	Up to 328 ft (100 m)
Type	Cat6 STP 22-24 AWG
Connector	10 pin circular- all-weather, impact resistant

CAMERA ACCESSORIES

Part #	VS-UNI-POLE-MNT
Description	Single Fixed Camera Mount/Bracket

VLP COMMUNICATIONS BOX

The VLP Comms Box combines processing and power in a durable, ruggedized enclosure that is equipped with an all-in-one built-in processor with GPS and PoE for up to four cameras.



SYSTEM

CPU	Intel Gen8 Core i7-8700T (12M Cache 2.4GHz up to 4.0GHz)
Memory	2 x 8GB DDR4 2400 MHz SO-DIMM
LAN Chipset	9 x Intel i210-AT and 1 x i219 (iAMT9.5 w/ i5, i7 only) Gb/s Ethernet Controllers Onboard Support PXE and WOL

I/O

Serial Port	3 x RS 232/422/485 (Auto Direction Control)
USB Port	4 x USB 3.0 Ports
LAN	10 x RJ45 Ports for GbE (Optional for M12 connector and 8 x PoE total Max. 120W)
Video Port	3 x DP Ports
Wi-Fi Adapter	802.11n/g/b
4G LTE / GPS	Sierra Wireless EM7511-Dual Sim Support

POWER REQUIREMENT

Power Input	120V AC
Power Protection	Automatic Recovery - Short Circuit Protection
Power Management	Remote/Ignition connection to toggle power
Power Off Control	Power off Delay Time Setting by BIOS and Software

SOFTWARE

Operating System	Ubuntu 18.04 64bit
------------------	--------------------

GRAPHICS

Graphics Intel	Intel® UHD Graphics 630
Resolution	Max Resolution (DP) : 4096x2304@60Hz

STORAGE

Type	2 x 2.5" Drive Bay for SATA Type HDD/SSD RAID 0, 1, 5 1 x mSATA
------	---

ENVIRONMENTAL

Operating Temp.	-40°C ~ 70°C, ambient w/ 0.6m/s airflow
Storage Temp.	-40°C ~ 80°C
Relative Humidity	10% RH – 90% RH (non-condensing)
Vibration (random)	EC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis with SSD
Vibration Operating	MIL-STD-810G, Method 514.6, Procedural, Category 4
Shock	Operating: MIL-STD-810G, Method 516.6, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD
Certifications	CE, FCC Class A, E13

MECHANICAL

Construction	Polycarbonate
Mounting Wall or pole mount	Wall or pole mount
Weight	5190g
Dimensions	260(L) x 250(W) x 95(H) mm



Ready to find out how we can work for you?



DRNdata.com | sales@DRNdata.com